

iPORT NTx-GigE Embedded Video Interface

Rapidly add high-performance GigE Vision 2.0 connectivity to systems and cameras



Overview

Pleora's **iPORT™ NTx-GigE Embedded Video Interface** hardware helps manufacturers shorten time-to-market, reduce risk, and lower costs by providing a straightforward way to integrate GigE Vision 2.0 video connectivity into cameras, x-ray detector panels, and imaging systems.

The NTx-GigE Embedded Video Interface interacts seamlessly with Pleora's other products in networked or point-to-point digital video systems. It complies with the GigE Vision® 2.0 and GenICam™ standards, ensuring interoperability in a multi-vendor environment.

The ultra-compact NTx-GigE is easily embedded into small-body cameras, flat-panel x-ray detectors, and imaging systems. Power over Ethernet (PoE) and external power options provide design flexibility, while lowering component and operating costs. The product supports the IEEE 1588 Precision Time Protocol to synchronize image capture functions and other system elements, enabling the exact triggering of image acquisition.

Pleora's iPORT NTx-GigE Embedded Video Interface is supported by:

- A Development Kit to help speed time-to-market by enabling the rapid design of prototypes and proof-of-concept demonstrations, often without requiring hardware development;
- The GenICam Integration Package (consisting of the iPORT AutoGen XML generation tool and a firmware reference design) which makes it fast and easy to create a user-friendly GenICam interface (contact sales for pricing information on this integration package).

Features

- Compact and low power
- GigE Vision and GenICam compatible
- Throughput approaching 1 Gb/s
- Up to 32-bit, 120 MHz parallel LVTTL/LVCMOS video input, and 4 interleaved taps
- Line scan and area scan modes
- 120 MB frame buffer to accommodate multi-mega pixel sensor sizes
- Supports both Power over Ethernet and external-powered options
- Updateable firmware via the GigE port for easy feature upgrades in the field

The iPORT NTx-GigE, together with the iPORT NTx-U3 for USB3 Vision™ connectivity family, are pin-compatible hardware solutions that provide manufacturers with a cost-effective approach to support all video interface needs.

iPORT NTx-GigE Embedded Video Interface

Hardware		Characteristics	
User Circuitry Interface	100-pin Samtec Connector: LSHM-150-04.0-L-DV-A-N-TR	Size (L x W x H)	37.0 mm x 37.0 mm x 28.1 mm (approximate, excluding RJ-45 Jack and GPIO board)
External Interface	<ul style="list-style-type: none"> 12-pin Hirose Connector: HR10A-10P-12P(73) 20-pin FCI Connector: 62674-201121ALF 	Weight	34 grams (includes NTx-GigE, GPIO board, 12-pin circular connector, and flat flex cable)
GigE Interface	RJ-45	Operating temperature	<ul style="list-style-type: none"> Commercial** Industrial** (-IND models)
GigE PHY	Marvell 88E1510	Storage temperature	-40°C to 85°C
FPGA	Altera Cyclone V	Power Supply	<ul style="list-style-type: none"> PoE Powered: IEEE 802.3af, up to 7 Watts Externally Powered: 4.8 to 16 Volts nominal
Image Buffer	120 MB 16-bit wide DDR3	Power Consumption	Less than 2.5 Watts when streaming at 1 Gbps
Persistent Memory	128 Mb Serial FLASH	MTBF at 40°C	1,318,440 hours
Clock Generator	Included	ECCN	EAR99
Inputs/Outputs on User Circuitry Interface			
Video Input	2.5 V LVTT/LVCMOS	Ordering Information	
GPIO Inputs	4 x 2.5 V LVTT/LVCMOS	900-6003	iPORT NTx-GigE OEM board set.
GPIO Outputs	4 x 2.5 V LVTT/LVCMOS	900-6004	iPORT NTx-GigE OEM Kit includes 900-6003, GPIO board with unsoldered 12-pin circular connector, and flat flex cable.
Serial (Bulk) Inputs*	3 x 2.5 V LVTT/LVCMOS	900-6005	iPORT NTx-GigE Development Kit includes 900-6003, GPIO board with soldered 12-pin circular connector and flat flex cable, NTx-Mini adapter board with 3 flat flex cables, prober board, Gigabit Ethernet desktop NIC, PoE power injector, 2 Ethernet cables, and eBUS SDK USB stick.
Serial (Bulk) Outputs*	3 x 2.5 V LVTT/LVCMOS	900-6006	iPORT NTx-GigE-IND OEM board set (industrial use).
Camera Control Outputs	4 x 2.5 V LVTT/LVCMOS	900-6007	iPORT NTx-GigE-IND OEM Kit (industrial use) includes 900-6006, GPIO board with unsoldered 12-pin circular connector, and flat flex cable.
GPIO on 12-Pin Circular Connector			
GPIO Inputs	4 connections routed to User Circuitry Interface	900-6008	iPORT NTx-GigE-IND Development Kit includes 900-6006, GPIO board with soldered 12-pin circular connector and flat flex cable, NTx-Mini adapter board with 3 flat flex cables, prober board, Gigabit Ethernet desktop NIC, PoE power injector, 2 Ethernet cables, and eBUS SDK USB stick.
GPIO Outputs	3 connections routed to User Circuitry Interface	900-6021	iPORT NTx-GigE Developer Bundle includes iPORT NTx-GigE Development Kit. Includes iPORT NTx-GigE OEM Board Set (900-6003), GPIO board with soldered 12-pin circular connector and flat flex cable, NTx-Mini adapter board with 3 flat flex cables, prober board, Gigabit Ethernet desktop NIC, PoE Power Injector, 2 Ethernet cables, eBUS SDK USB stick, and one year of eBUS SDK Developer Annual Maintenance and Support.
Serial Communications Input	Connection routed to User Circuitry Interface	900-6022	iPORT NTx-GigE-IND Developer Bundle includes iPORT NTx-GigE-IND Development Kit. Includes 900-6006, GPIO board with soldered 12-pin circular connector and flat flex cable, NTx-Mini adapter board with 3 flat flex cables, prober board, Gigabit Ethernet desktop NIC, PoE Power Injector, 2 Ethernet cables, eBUS SDK USB stick, and one year of eBUS SDK Developer Annual Maintenance and Support.
Serial Communications Output	Connection routed to User Circuitry Interface		
Frame Grabber			
Number of Channels	1		
Scan Modes	Area Scan (Progressive) and Line Scan		
Pixel Depth (bits)	8, 10, 12, 14, 16, 24, 32		
Pixel Clock	<ul style="list-style-type: none"> Min: 20 MHz Max: 120 MHz 		
Taps per Data Channel	Up to 4		
Image Width (pixels)	<ul style="list-style-type: none"> Min: 8 Default: 640 Max: 16,376 Increment: 4 		
Image Height (pixels)	<ul style="list-style-type: none"> Min: 1 Default: 480 Max: 16,383 Increment: 1 		
Windowing/Region of Interest	Yes		
Tap Reconstruction	Interleaved only		

* Various serial communication protocols are supported.

** Case and junction temperature limits vary by IC device. Please refer to User Guide for specific IC operating temperature specifications and thermal management information.